

ZONEPLUS SERIES 2 Motorised Valves

Detach Button

A range of motorised valves that combine proven electronic controls technology with the latest Horstmann design features, for easy installation and maintenance.


There are four models within the range: 22mm & 28mm 2 port spring return valves 22mm & 28mm 3 port mid-position valves


Horstmann. Together, we're in control.

Horstmann. Together, we're in control.



ZONEPLUS F322 3 Port 22mm mid-position valve and **ZONEPLUS F328** 3 Port 28mm mid-position valve






	Α	В	C	D
F322m	55	110	91	139
F328m	60	120	91	143

ZONEPLUS F222 2 Port 22mm spring return zone valve and **ZONEPLUS F228** 2 Port 28mm spring return zone valve (both with auxiliary switch).

SPECIFICATION

CONTACT AND CABLE RATING 5 AMPS 230V AC MOTOR POWER SUPPLY 230V AV 50Hz MOTOR POWER CONSUMPTION <6 5W LEAD SUPPLIED 1 Metre, 5 core – industry standard colours used EARTH CONNECTION REQUIRED MAXIMUM AMBIENT TEMPERATURE +50°C MAXIMUM FLUID TEMPERATURE +80°C MAXIMUM DIFFERENTIAL PRESSURE 1 Bar MAXIMUM STATIC PRESSURE 21 Bar MATERIALS: Ball: ethylene propylene dio mono (epdm) Cover: thermoplastic Valve body: brass PIPE FITTING SIZE F222m & F322m - 22mm compression F228m & F328m - 28mm compression ACTUATOR Energised – power open De-energised – spring return closed OVERRIDE LEVER







	Α	В	C	D
F222m	55	110	91	112
F228m	60	120	91	114


Plumbing Data

1. Typical layout for fully pumped system using F222 or F228 valves.

2. Typical layout for fully pumped system using F322 or F328 valves.

٢Ö

Ó





Horstmann Controls Limited, South Bristol Business Park, Roman Farm Road, Bristol BS4 1UP. Tel: 0117 978 8700 Fax: 0117 978 8701 E-mail: sales@horstmann.co.uk Web: www.horstmann.co.uk A division of Horstmann Group Ltd. Registered office: PRI House, Moorside Road, Winnall Trading Estate, Winchester, Hampshire S023 7RX. Registered in England No. 457553