

## *Ballofix isolating service valves*





**PEGLER**

## Ballofix isolating service valves

# Pegler Ballofix isolating service valves for potable water,

*From its introduction more than fifty years ago the Pegler Ballofix ball valve concept has been the benchmark for innovative flow control. Pegler Ballofix ball valves offer reliable, cost-effective whole-life solutions for a wide variety of applications, including public buildings and commercial properties.*


*Over the years the range has evolved so that today it not only offers traditional compression and threaded end connections, but also the option of time-saving press-fit and push-fit connections for even greater flexibility on site. An added advantage of Pegler Ballofix is that it provides easy visual identification of the service the valve is used for with the option of a choice of colour-coded handles and, in the case of gas services, a yellow painted body valve.*

### **Handle options:**

*Black: for general services. Blue: for cold water services.*

*Red: for hot water services.*

*Chrome plated: for aesthetics, or complete yellow valve for gas.*



*Ballofix bodies and handles are designed to provide easy identification of the service for which they are being used.*

## Push-fit

### Quick and easy to install.

*Pegler Ballofix valves with push-fit connections offer the advantage of being much quicker to fit than more traditional end connections, saving both time and money on site.*



hot and cold water, oil, compressed air and gas services.

## Lockable

**A tamper-proof solution for a wide range of public buildings.**

*For locations where even greater protection is required Pegler Ballofix Lockable is the obvious choice. Pegler Ballofix Lockable valves prevent unwanted and unauthorised opening or closing of the water supply and are a popular option for schools, institutions and public buildings.*

*They are also recommended to help protect water resources where water meters apply, and are an effective solution for water authorities in dealing with non payment of water rates. The top part of the valves has a tamperproof lock which can be operated by the key only. The lock is equipped with a master key, ensuring that only one key is necessary for several locks.*



## Filter valves

**All the protection you need from system debris.**

*The Pegler Ballofix range also includes filter valves which offer protection against damage caused by debris in pipework and are particularly effective and important in installations featuring expensive equipment and systems such as shower valves, electronic taps, thermostatic mixing valves and ceramic-disc taps and mixers.*






**PEGLER**

## Ballofix isolating service valves

*New easy-to-use handle with ergonomic design available in colours for easy identification of services*

**WRAS**  
APPROVED  
PRODUCT



*New construction that makes ball rotation smoother*

*New design with exclusive installation finish*

*Choice of body finishes*

### **Pegler Ballofix benefits and features include:**

- Proven quality, reliability and long-term value for money
- Continuous improvement and development to anticipate and satisfy ever-changing needs
- Comprehensive choice of valves and end connections, including new press-fit and push-fit
- Low maintenance costs
- Components can be replaced without the need to close down the whole system
- Mounting is independent of flow direction
- Operated by wrench, screwdriver or handle (the latter can be screwed into the ball and ensures a better torque)
- Positive internal stop
- Individually 100% tested
- WRAS approved

# Ballofix isolating service valves

## Valve connection overview

As well as offering traditional threaded and compression connections the Pegler Ballofix valves range also offers the new connection technology of press-fit and push-fit jointing and sets a new standard for the industry.



### Press-fit connections

A quick, clean, heat-free jointing technology for copper, stainless steel and carbon steel pipe work up to 22mm.

#### Features

- Unique design and using bronze permits jointing of all materials – one connector fits all
- Simple and fast, reduces time on site with good repetition of joint quality
- Uses one simple, inexpensive tool with no additional materials
- Intrinsically clean, no flushing to remove residues
- No hot works permits and associated insurance implications or health & safety hazards
- Suitable for both heating, chilled and potable water
- M-Jaw product.



### Push-fit connections

A fast, cost effective jointing system ideal for copper and carbon steel, with joints created in seconds without complex clamping, the application of heat and extended preparation and adhesive curing delays.

#### Features

- Major time savings
- Permits rapid installation and removal (if required)
- No special tools required
- Heat-free for enhanced safety, with no localised annealing
- Allows working on filled systems
- No carbon deposits, reduced corrosion risk
- Perfectly clean internal bore, less finishing/cleaning.



### Threaded connections

A heat-free jointing method particularly suited to smaller, fixed systems using EN10255 mild steel tube, where the installation is expected to remain unchanged for long periods of time.

#### Features

- Parallel thread, ISO 228-1
- Suitable for both heating, chilled and potable water
- Ergonomically shaped handle.



### Compression connections

A traditional heat-free mechanical jointing system making it easy to undo and re-make joints. Ideal for applications where maintenance and repair are required.


#### Features

- Major time saving compared to soldering and brazing
- Intrinsically clean, no flushing to remove residues
- No hot works permits and associated insurance implications
- Suitable for heating, cooling and potable water applications.

## Press-fit valves

### Ballofix DZR isolating ball valves

**WRAS**  
APPROVED  
PRODUCT




#### Ballofix Isolating ball valve – straight pattern

*XPress ends for copper/carbon steel/stainless steel tube.  
Screw driver slot. DZR, chrome finish*

| Size | Pattern No | A  | Weight kg | Order code |
|------|------------|----|-----------|------------|
| 15mm | 4381ZA     | 83 | 0.16      | 13060      |
| 22mm | 4481ZA     | 88 | 0.20      | 13061      |

**WRAS**  
APPROVED  
PRODUCT




#### Ballofix Isolating ball valve – straight pattern

*XPress ends for copper/carbon steel/stainless steel tube.  
Black plastic handle, DZR, chrome finish*

| Size | Pattern No | A  | Weight kg | Order code |
|------|------------|----|-----------|------------|
| 15mm | 4381ZP     | 83 | 0.17      | 13062      |

**WRAS**  
APPROVED  
PRODUCT



#### Ballofix Isolating ball valve – straight pattern

*XPress end for copper/carbon steel/stainless steel tube x male end.  
Screw driver slot, DZR, chrome finish*

| Size        | Pattern No | A    | Weight kg | Order code |
|-------------|------------|------|-----------|------------|
| 15mm x 1/2" | 8310ZA     | 59.2 | 0.12      | 13260      |
| 18mm x 3/4" | 8410ZA     | 62.6 | 0.15      | 13261      |
| 22mm x 3/4" | 8510ZA     | 62.9 | 0.17      | 13262      |

## Push-fit valves


### Ballofix DZR isolating ball valves

#### Ballofix Isolating ball valve – straight pattern

*Tectite push-fit ends for copper and carbon steel tube,  
Screw driver slot, DZR, chrome finish*

| Size | Connection | Pattern No. | A   | Weight kg | Order code |
|------|------------|-------------|-----|-----------|------------|
| DN15 | 15mm       | 6381Z       | 85  | 0.14      | 13073      |
| DN20 | 22mm       | 6481Z       | 100 | 0.20      | 13074      |

**WRAS**  
APPROVED  
PRODUCT




#### Ballofix Isolating ball valve – straight pattern

*Tectite push-fit ends for copper and carbon steel tube,  
plastic lever operation, DZR, chrome finish*

| Size | Connection | Pattern No. | A   | Weight kg | Order code |
|------|------------|-------------|-----|-----------|------------|
| DN15 | 15mm       | 6381ZP      | 85  | 0.15      | 13081      |
| DN20 | 22mm       | 6481ZP      | 100 | 0.21      | 13082      |

**WRAS**  
APPROVED  
PRODUCT




#### Ballofix Isolating ball valve – straight pattern

*Tectite push-fit end for copper and carbon steel tube x male end,  
Screw driver slot, DZR, chrome finish*

| Size | Connection  | Pattern No. | A    | Weight kg | Order code |
|------|-------------|-------------|------|-----------|------------|
| DN15 | 15mm x 1/2" | 7310ZA      | 62.1 | 0.12      | 13263      |

**WRAS**  
APPROVED  
PRODUCT




#### Ballofix Isolating ball valve – straight pattern

*Tectite push-fit end for copper and carbon steel tube x female end,  
Screw driver slot, DZR, chrome finish*

| Size | Connection  | Pattern No. | A    | Weight kg | Order code |
|------|-------------|-------------|------|-----------|------------|
| DN15 | 15mm x 1/2" | 7331ZA      | 62.1 | 0.13      | 13264      |


**WRAS**  
APPROVED  
PRODUCT



## Threaded valves

### Ballofix DZR threaded isolating ball valves

**WRAS**  
APPROVED  
PRODUCT




#### Ballofix isolating ball valve – threaded

Male x male, chrome plated, screw driver operation, DZR, chrome finish

| Size        | A  | Weight kg | Order code |
|-------------|----|-----------|------------|
| 1/2" 3390ZA | 45 | 0.10      | 13356      |

**WRAS**  
APPROVED  
PRODUCT




#### Ballofix isolating ball valve – threaded

Female x female, screw driver operation, DZR, plain finish

| Size        | A  | Weight kg | Order code |
|-------------|----|-----------|------------|
| 1/4" 3205YA | 45 | 0.09      | 13158      |
| 1/2" 3350YA | 47 | 0.11      | 13532      |
| 3/4" 3450YA | 65 | 0.23      | 13559      |
| 1" 3550YA   | 62 | 0.42      | 13573      |

**WRAS**  
APPROVED  
PRODUCT




#### Ballofix isolating ball valve – threaded

Female x female, screw driver operation, DZR, chrome finish

| Size               | A  | Weight kg | Order code |
|--------------------|----|-----------|------------|
| 1/4" x 1/4" 3205ZA | 45 | 0.08      | 13161      |
| 3/8" x 3/8" 3250ZA | 46 | 0.07      | 13189      |
| 1/2" x 1/2" 3350ZA | 47 | 0.11      | 13535      |
| 3/4" x 3/4" 3450ZA | 65 | 0.23      | 13560      |

**WRAS**  
APPROVED  
PRODUCT



#### Ballofix isolating ball valve – threaded

Male x female, screw driver operation, DZR, plain finish

| Size               | A  | Weight kg | Order code |
|--------------------|----|-----------|------------|
| 1/4" x 1/4" 3200YA | 44 | 0.07      | 13148      |
| 3/8" x 3/8" 3210YA | 45 | 0.06      | 13166      |
| 1/2" x 1/2" 3310YA | 44 | 0.10      | 13538      |
| 3/4" x 3/4" 3410YA | 63 | 0.20      | 13374      |
| 1" x 1" 3510YA     | 61 | 0.36      | 13445      |




### Ballofix isolating ball valve – threaded

Male x female, chrome plated, screw driver operation, DZR, chrome finish

| Size                      | A  | Weight kg | Order code |
|---------------------------|----|-----------|------------|
| 1/4" x 1/4" <b>3200ZA</b> | 44 | 0.07      | 13151      |
| 1/2" x 1/2" <b>3310ZA</b> | 44 | 0.26      | 13539      |
| 3/4" x 3/4" <b>3410ZA</b> | 63 | 0.19      | 13377      |
| 1" x 1" <b>3510ZA</b>     | 61 | 0.36      | 13448      |

WRAS  
APPROVED  
PRODUCT




### Ballofix isolating ball valve – threaded

Male x female, plastic lever operation, DZR, plain finish

| Size                      | A  | Weight kg | Order code |
|---------------------------|----|-----------|------------|
| 1/2" x 1/2" <b>3310YP</b> | 44 | 0.10      | 13226      |

WRAS  
APPROVED  
PRODUCT




### Ballofix isolating ball valve – threaded

Male x female, chrome plated, plastic lever operation, DZR, chrome finish

| Size                      | A  | Weight kg | Order code |
|---------------------------|----|-----------|------------|
| 1/2" x 1/2" <b>3310ZP</b> | 44 | 0.10      | 13228      |

WRAS  
APPROVED  
PRODUCT




### Ballofix radiator valve – straight pattern

BSP parallel female thread x male iron union, screw driver operation, DZR, plain finish

| Size               | A  | Weight kg | Order code |
|--------------------|----|-----------|------------|
| 3/4" <b>5060BA</b> | 82 | 0.37      | 13367      |

WRAS  
APPROVED  
PRODUCT




## Ballofix Lockable

### Ballofix isolating ball valve – straight pattern

RP female threads, key lock and hexagon key operation, brass, plain finish


| Size | Connection | Pattern No. | A     | Weight kg | Order code |
|------|------------|-------------|-------|-----------|------------|
| DN15 | 1/2"       | 3355BK      | 57    | 0.23      | 13219      |
| DN20 | 3/4"       | 3455BK      | 62.5  | 0.36      | 13360      |
| DN25 | 1"         | 3555BK      | 75.5  | 0.56      | 13443      |
| DN40 | 1 1/2"     | 3755BK      | 98.0  | 1.23      | 13222      |
| DN50 | 2"         | 3855BK      | 115.0 | 2.28      | 13223      |

WRAS  
APPROVED  
PRODUCT



## Threaded valves


**WRAS**  
APPROVED  
PRODUCT



### Ballofix filter valve

*BSP parallel female ends, plastic lever operation, DZR, chrome finish*

| Size                | A  | Weight kg | Order code |
|---------------------|----|-----------|------------|
| 1/2" <b>33624ZP</b> | 45 | 0.12      | 14814      |




### Ballofix gas valve

*BSP taper female ends, screw driver operation, painted yellow finish*

| Size                 | A  | Weight kg | Order code |
|----------------------|----|-----------|------------|
| 1/2" <b>33504BGA</b> | 56 | 0.14      | 13282      |

**WRAS**  
APPROVED  
PRODUCT




### Ballofix draincock

*Screw driver operation, DZR, chrome finish*

| Size                             | A  | Weight kg | Order code |
|----------------------------------|----|-----------|------------|
| 1/2" <b>5095CA</b> Chrome Plated | 26 | 0.08      | 13176      |
| 1/2" <b>5095BA</b> Nickel        | 26 | 0.08      | 13175      |

**WRAS**  
APPROVED  
PRODUCT



### Ballofix radiator valve – angle pattern

*Compression x male iron union, screw driver operation, DZR, chrome finish*

| Size                      | A  | Weight kg | Order code |
|---------------------------|----|-----------|------------|
| 15mm x 1/2" <b>5045CA</b> | 59 | 0.28      | 13242      |


# Compression valves

## Compression check valves

### Ballofix double check valve Compression ends, DZR, plain finish

| Size               | A   | Weight kg | Order code |
|--------------------|-----|-----------|------------|
| 15mm <b>0015YA</b> | 100 | 0.20      | 13521      |


WRAS  
APPROVED  
PRODUCT



### Ballofix double check valve Compression ends, DZR, chrome finish

| Size               | A   | Weight kg | Order code |
|--------------------|-----|-----------|------------|
| 15mm <b>0015ZA</b> | 100 | 0.20      | 13522      |

WRAS  
APPROVED  
PRODUCT




## Ballofix compression isolating ball valves

### Ballofix isolating ball valve – straight pattern Compression ends. Screwdriver operation. DZR, plain finish

| Size               | A  | Weight kg | Order code |
|--------------------|----|-----------|------------|
| 15mm <b>3381YA</b> | 41 | 0.14      | 13540      |
| 22mm <b>3481YA</b> | 57 | 0.22      | 13563      |
| 28mm <b>3581YA</b> | 65 | 0.54      | 13575      |


WRAS  
APPROVED  
PRODUCT



### Ballofix isolating ball valve – straight pattern Compression ends. Screwdriver operation. DZR, chrome finish

| Size               | A  | Weight kg | Order code |
|--------------------|----|-----------|------------|
| 15mm <b>3381ZA</b> | 41 | 0.14      | 13543      |
| 22mm <b>3481ZA</b> | 57 | 0.22      | 13564      |
| 28mm <b>3581ZA</b> | 65 | 0.54      | 13576      |


WRAS  
APPROVED  
PRODUCT



### Ballofix isolating ball valve – straight pattern Compression ends. Plastic lever operation. DZR brass, plain finish

| Size               | A  | Weight kg | Order code |
|--------------------|----|-----------|------------|
| 15mm <b>3381YP</b> | 41 | 0.17      | 13541      |


WRAS  
APPROVED  
PRODUCT





## Compression valves


**WRAS**  
APPROVED  
PRODUCT



### Ballofix isolating ball valve – straight pattern Compression ends. Plastic CP lever operation. DZR, chrome finish

| Size               | A  | Weight kg | Order code |
|--------------------|----|-----------|------------|
| 15mm <b>3381ZM</b> | 41 | 0.17      | 13545      |


**WRAS**  
APPROVED  
PRODUCT



### Ballofix isolating ball valve – straight pattern Compression ends. Black plastic lever operation. DZR, chrome finish

| Size               | A  | Weight kg | Order code |
|--------------------|----|-----------|------------|
| 15mm <b>3381ZP</b> | 41 | 0.15      | 13544      |


**WRAS**  
APPROVED  
PRODUCT



### Ballofix isolating ball valve – straight pattern Compression x BSP parallel female thread. Screwdriver operation. DZR, plain finish

| Size               | A  | Weight kg | Order code |
|--------------------|----|-----------|------------|
| 15mm <b>3331YA</b> | 51 | 0.12      | 13530      |
| 22mm <b>3431YA</b> | 53 | 0.25      | 13384      |


**WRAS**  
APPROVED  
PRODUCT



### Ballofix isolating ball valve – straight pattern Compression x BSP parallel female thread. Screwdriver operation. DZR, chrome finish

| Size               | A  | Weight kg | Order code |
|--------------------|----|-----------|------------|
| 15mm <b>3331ZA</b> | 51 | 0.10      | 13531      |


**WRAS**  
APPROVED  
PRODUCT



### Ballofix isolating ball valve – straight pattern Compression x BSP parallel female thread. Plastic lever operation. DZR, plain finish

| Size               | A  | Weight kg | Order code |
|--------------------|----|-----------|------------|
| 15mm <b>3331YP</b> | 51 | 0.13      | 13233      |

**WRAS**  
APPROVED  
PRODUCT




### Ballofix isolating ball valve – straight pattern Compression x BSP parallel female thread. Plastic lever operation. DZR, chrome finish

| Size               | A  | Weight kg | Order code |
|--------------------|----|-----------|------------|
| 15mm <b>3331ZP</b> | 51 | 0.13      | 13236      |

**Ballofix isolating ball valve – straight pattern**  
*Compression x BSP parallel male thread. Screwdriver operation. DZR, plain finish*

| Size               | A  | Weight kg | Order code |
|--------------------|----|-----------|------------|
| 15mm <b>3375YA</b> | 40 | 0.13      | 13311      |


WRAS  
APPROVED  
PRODUCT



**Ballofix radiator valve - straight pattern**  
*Compression x male iron union. Screwdriver operation. DZR, chrome finish*

| Size                      | A  | Weight kg | Order code |
|---------------------------|----|-----------|------------|
| 15mm x 1/2" <b>5035CA</b> | 69 | 0.24      | 13248      |


WRAS  
APPROVED  
PRODUCT



**Ballofix isolating ball valve – angle pattern**  
*Compression ends. Screwdriver operation. DZR, plain finish*

| Size               | A  | Weight kg | Order code |
|--------------------|----|-----------|------------|
| 15mm <b>3380YA</b> | 20 | 0.12      | 13321      |


WRAS  
APPROVED  
PRODUCT



**Ballofix isolating ball valve – angle pattern**  
*Compression ends. Screwdriver operation. DZR, chrome finish*

| Size               | A  | Weight kg | Order code |
|--------------------|----|-----------|------------|
| 15mm <b>3380ZA</b> | 23 | 0.12      | 13324      |

WRAS  
APPROVED  
PRODUCT



**Ballofix isolating ball valve – angle pattern**  
*Compression ends. Plastic lever operation. DZR, plain finish*

| Size               | A  | Weight kg | Order code |
|--------------------|----|-----------|------------|
| 15mm <b>3380YP</b> | 20 | 0.13      | 13323      |

WRAS  
APPROVED  
PRODUCT



**Ballofix isolating ball valve – angle pattern**  
*Compression ends. Plastic lever operation. DZR, chrome finish*

| Size               | A  | Weight kg | Order code |
|--------------------|----|-----------|------------|
| 15mm <b>3380ZP</b> | 20 | 0.13      | 13326      |

WRAS  
APPROVED  
PRODUCT



## Compression valves


**WRAS**  
APPROVED  
PRODUCT



### Ballofix minibore isolating ball valve – straight pattern Compression ends. Screwdriver operation. DZR, plain finish

| Size               | A  | Weight kg | Order code |
|--------------------|----|-----------|------------|
| 15mm <b>1581YA</b> | 20 | 0.11      | 13108      |

**WRAS**  
APPROVED  
PRODUCT




### Ballofix minibore isolating ball valve – straight pattern Compression ends. Screwdriver operation. DZR, chrome finish

| Size               | A  | Weight kg | Order code |
|--------------------|----|-----------|------------|
| 15mm <b>1581ZA</b> | 41 | 0.11      | 13111      |

## Ballofix service valves


**WRAS**  
APPROVED  
PRODUCT



### Ballofix service valve – straight swivel pattern Compression x BSP union nut. Screwdriver operation. DZR, plain finish

| Size                      | A  | Weight kg | Order code |
|---------------------------|----|-----------|------------|
| 15mm x 1/2" <b>3140YA</b> | 41 | 0.12      | 13658      |


**WRAS**  
APPROVED  
PRODUCT



### Ballofix service valve – straight swivel pattern Compression x BSP union nut. Screwdriver operation. DZR, chrome finish

| Size                      | A  | Weight kg | Order code |
|---------------------------|----|-----------|------------|
| 15mm x 1/2" <b>3140ZA</b> | 41 | 0.12      | 13133      |


**WRAS**  
APPROVED  
PRODUCT



### Ballofix service valve – straight swivel pattern Compression x BSP union nut. Plastic lever operation. DZR, chrome finish

| Size                      | A  | Weight kg | Order code |
|---------------------------|----|-----------|------------|
| 15mm x 1/2" <b>3140ZP</b> | 41 | 0.13      | 13135      |

**WRAS**  
APPROVED  
PRODUCT



### Ballofix service valve – angle swivel pattern Compression x BSP union nut. Screwdriver operation. DZR, plain finish


| Size               | A  | Weight kg | Order code |
|--------------------|----|-----------|------------|
| 15mm <b>3160YA</b> | 22 | 0.14      | 13523      |



**Ballofix service valve – angle swivel pattern**  
*Compression x BSP union nut. Screwdriver operation. DZR, chrome finish*

| Size               | A  | Weight kg | Order code |
|--------------------|----|-----------|------------|
| 15mm <b>3160ZA</b> | 22 | 0.14      | 13143      |

**WRAS**  
APPROVED PRODUCT




*Ballofix filter valves*

**Ballofix filter valve**  
*Compression ends. Screwdriver operation. Removable filter. DZR, chrome finish*

| Size                | A  | Weight kg | Order code |
|---------------------|----|-----------|------------|
| 15mm <b>33615ZA</b> | 45 | 0.16      | 13304      |
| 22mm <b>34622ZA</b> | 50 | 0.27      | 13416      |


**WRAS**  
APPROVED PRODUCT



**Ballofix filter valve**  
*Compression ends. Plastic lever operation. DZR, chrome finish*

| Size                | A  | Weight kg | Order code |
|---------------------|----|-----------|------------|
| 15mm <b>33615ZP</b> | 45 | 0.16      | 13305      |

**WRAS**  
APPROVED PRODUCT



## Compression valves

### Ballofix compression valve accessories



#### Small plastic handle - push in

*Order code*

**CPT0059** Black 13712



#### Large plastic handle - push in

*Order code*

**CPT0073** Black 13721



#### Small plastic handle - screw fixed

*Order code*

**ERG** Black 13724  
**ERG** Red 13728  
**ERG** Blue 13729  
**ERG** Chrome 13732



#### Large plastic handle - screw fixed

*Order code*

**ERG** Black 13725

## Flow regulator insert

To maintain a defined flow rate

| Size | Flow rate | Colour | Order code |
|------|-----------|--------|------------|
| 15mm | 4 l/m     | Pink   | 13779      |
| 15mm | 6 l/m     | Grey   | 13780      |
| 15mm | 8 l/m     | White  | 13781      |
| 15mm | 9/10 l/m  | Yellow | 13782      |
| 15mm | 12 l/m    | Brown  | 13783      |
| 22mm | 12 l/m    | Orange | 13784      |
| 22mm | 18 l/m    | Brown  | 13785      |



## Compression nuts

### Compression nut

Brass, plain finish

| Size                | Order code |
|---------------------|------------|
| 15mm <b>CPT0021</b> | 14853      |
| 22mm <b>CPT0023</b> | 13686      |



### Compression nut

Brass, commercial chrome finish

| Size                | Order code |
|---------------------|------------|
| 15mm <b>CPT0022</b> | 13685      |
| 22mm <b>CPT0024</b> | 14854      |



### Compression ring

Brass, plain finish

| Size                | Order code |
|---------------------|------------|
| 15mm <b>CPT0044</b> | 13698      |
| 22mm <b>CPT0045</b> | 13699      |







# Pegler Yorkshire

## Our brands:



## UK sales

Free Phone: 0800 156 0010  
Free Fax: 0808 156 1011  
Email: [uk.sales@pegleryorkshire.co.uk](mailto:uk.sales@pegleryorkshire.co.uk)

## Export

Tel: +44 (0) 1302 855 656  
Fax: +44 (0) 1302 730 513  
Email: [export@pegleryorkshire.co.uk](mailto:export@pegleryorkshire.co.uk)

## Technical Help

Free Phone: 0800 156 0050  
Free Fax: 0808 156 1012  
Email: [tech.help@pegleryorkshire.co.uk](mailto:tech.help@pegleryorkshire.co.uk)

## Brochure Hotline

Free Phone: 0800 156 0020  
Free Fax: 0808 156 1011  
Email: [info@pegleryorkshire.co.uk](mailto:info@pegleryorkshire.co.uk)

[www.pegleryorkshire.co.uk](http://www.pegleryorkshire.co.uk)

## Pegler Yorkshire Group Limited

St. Catherine's Avenue, Doncaster,  
South Yorkshire, DN4 8DF, England.  
Tel: 0844 243 4400 Fax: 0844 243 9870

Registered in England Company No. 00401507  
Registered Office: Haigh Park Road, Stourton, Leeds,  
West Yorkshire, LS10 1RT, England.

All brand names and logo styles are registered trademarks.  
Maintaining a policy of continual product development,  
Pegler Yorkshire reserves the right to change specifications, design  
and materials of products listed in this publication without prior notice.

LIT.REF: 880109.04.11