Product Facts

Sentinel Seal X

External Joint & Leak Sealer for Central Heating Systems

Features & Benefits

- Easy to apply one component sealant
- Excellent adhesion to non-porous surfaces
- Fast cure tack free in 30 minutes
- Unaffected by extremes in temperature
- Retains flexibility after curing
- Non-staining
- Manufactured under a quality system conforming to ISO9001

Application

Sentinel Seal X is a one component, ready to use, moisture curing, low modulus silicone sealant. It can be applied to screwed fittings, compression joints and gaskets to form a water and air tight seal. A well pasted cloth may be bound around burst or leaking pipes to form a temporary repair.

Instructions

- 1. Relieve water pressure until curing is complete.
- Ensure that surfaces are free of rust, grease, oil, release agents, dust, dirt, old sealants and other contaminants that might impair adhesion.
- Apply product from tube, and replace cap immediately. Complete 'tooling' within 5 to 10 minutes.
- 4. Curing time depends on the thickness applied, and the humidity. Spraying with water assists curing.



Physical Properties

- Appearance:
- Odour: Acetic acid
 - Specific gravity:
 - /: 1.00 (25°C)

White paste

• pH (concentrated product): 2.5

Packaging

• 50 ml tube

Safety Precautions

The information provided overleaf enables compliance with the Control of Substances Hazardous to Health Regulations. A full Safety Data Sheet is available upon request.



www.sentinel-solutions.net

Sentinel Performance Solutions Ltd, The Heath Business & Technical Park Runcorn, Cheshire, WA7 4QX T: +44 (0) 1928 588330 F: +44 (0) 01928 588368 Page 1 of 2

Seal X Joint & Leak Sealer

Seal X Joint & Leak Sealer	A silicone based paste.
Health Hazards	Non-hazardous when used normally.
Handling	Avoid eye contact.
	Avoid prolonged or repeated contact with skin.
	Do not breathe vapour.
	Wash after handling, especially before eating, drinking or smoking.
	Keep out of reach of children and animals.
Storage	Keep in original container.
Spillage	Scrape up and place in container fitted with a lid.
Fire/Explosion Risks	Non-flammable
First Aid	Skin Exposure :
	Wipe off excess.
	Wash thoroughly with soap and water.
	Immediately remove contaminated clothing.
	Eye Exposure :
	Flush immediately with plenty of running water. Keep eyelids apart.
	Seek medical attention.
	Ingestion :
	First physically remove any material from mouth, then rinse mouth
	with water.
	Give plenty of milk or water to drink.
	Do NOT induce vomiting!

www.sentinel-solutions.net

Sentinel Performance Solutions Ltd, The Heath Business & Technical Park Runcorn, Cheshire, WA7 4QX T: +44 (0) 1928 588330 F: +44 (0) 01928 588368 Page 2 of 2

