



HORSTMANN



425 SERIES Electro-mechanical Programmable

Horstmann's best selling, big value 425 Series programmers are the simplest way to control hot water and central heating in the home.

Simple to use with easily understood settings adjusted in seconds

Easy to install using a nine pin backplate

Advance control to allow manual override ON or OFF

Programme options: ON, OFF, All Day or Auto

**Horstmann.
Together,
we're in control.**



Horstmann. Together, we're in control.

SPECIFICATION

425 TIARA & DIADEM

CONTACT RATING
Double circuit 6 (2.5) Amps
230V AC

CONTACT TYPE
Micro-disconnection changeover
Voltage free (Tiara only)

MOTOR
Synchronous 230V 50Hz
Double insulated

POWER CONSUMPTION
2.5W

DIRT PROTECTION
Normal situations

MOISTURE PROTECTION
Ordinary

ENCLOSURE PROTECTION
IP 20

MAXIMUM OPERATING TEMPERATURE
+55°C

DIAL SETTING
2 ON, 2 OFF tappets
Min. ON/OFF period 45 mins

DIMENSIONS
152mm x 107mm x 39mm

MOUNTING
9 Pin wall fixing plate

425 CORONET

CONTACT RATING
Single circuit 13 (6) A 230V AC

CONTACT TYPE
Micro-disconnection changeover
Voltage free

MOTOR
Synchronous 230V 50Hz
Double insulated

POWER CONSUMPTION
2.5W

DIRT PROTECTION
Normal situations

MOISTURE PROTECTION
Ordinary

ENCLOSURE PROTECTION
IP 20

MAXIMUM OPERATING TEMPERATURE
+55°C

DIAL SETTING
2 ON, 2 OFF tappets
Min. ON/OFF period 45 mins

DIMENSIONS
152mm x 107mm x 39mm

MOUNTING
9 Pin wall fixing plate



425 DIADEM

This twin circuit, hot water and central heating programmer, with indicator lights, has 16 programmes available for fully pumped systems, including independent programming of heating and hot water and 10 programmes for gravity HW/pumped CH systems.

The Diadem is ideal for gravity systems and fully pumped systems with zone valves.

425 TIARA

The Tiara has all the capability and features of the 425 Diadem, but without the indicator lights.

The Tiara is ideally suited for both gravity systems and fully pumped systems with either mid-position or zone valves.

425 CORONET

A single circuit timeswitch for straightforward, accurate time control.

The 425 Coronet is particularly suitable for combi boiler systems, warm air systems and extra zone control.

	Single Circuit	Twin Circuit	Permanent ON/OFF	ON all day	ON/OFF twice a day	Combi-boiler	Pumped Systems	Gravity HW	Independent CH/HW	Immersion Heaters	Indicator Lights
425 Diadem		●	●	●	●		●	●	●		●
425 Tiara		●	●	●	●		●	●	●		
425 Coronet	●		●	●	●	●				●	



HORSTMANN

Horstmann Controls Limited, South Bristol Business Park, Roman Farm Road, Bristol BS4 1UP.
Tel: 0117 978 8700 Fax: 0117 978 8701 E-mail: sales@horstmann.co.uk Web: www.horstmann.co.uk
A division of Horstmann Group Ltd. Registered office: PRI House, Moorside Road, Winnall Trading Estate, Winchester, Hampshire SO23 7RX.
Registered in England No. 457553
©March 2009: Horstmann Group Ltd. All rights reserved. The company reserves the right to alter product specifications without notice.