

OPTIONAL DUCT KITS FOR VALOR ULTIMATE TURBOCHIM MODEL 517SF

Kit 517DK

Consists of:-

1 1.5m long duct.

This kit is intended for use where:

- i) The duct front covers and backing plates supplied with the appliance are of sufficient length to cover the total length of the duct run
- ii) But the shape of the building has meant that the ducts supplied with the appliance have had to be cut in such a way that an extra duct length with a connecting seal is needed.

Kit 517EBK

Consists of:-

1 90° Elbow duct

1 90° External bend duct cover

2 Spring cable clips

For use where the duct run goes round a 90° external corner.

For corner installations the ends of the plates must be mitred and butted together even when covered by the elbow front covers.

Small children could touch the hot ducting if there are any gaps between the top horizontal flanges or bottom angled flanges of the backing plates.

Support for the fan cable near the corner using the spring cable clips supplied in the pack. Fit the clips to the bottom edge of the backing plates and attach the cable.

A maximum of two elbow ducts can be used. The two elbows can be both internal, both external or one of each.

Note that the maximum total length of duct run where either one or two elbows are used is 3m

Kit 517IBK

Consists of:-

1 90° Elbow duct

1 90° Internal bend duct cover

2 Spring cable clips

For use where the duct run goes round a 90° internal corner.

For corner installations the ends of the plates must be mitred and butted together even when covered by the elbow front covers.

Small children could touch the hot ducting if there are any gaps between the top horizontal flanges or bottom angled flanges of the backing plates.

Support for the fan cable near the corner using the spring cable clips supplied in the pack. Fit the clips to the bottom edge of the backing plates and attach the cable.

A maximum of two elbow ducts can be used. The two elbows can be both internal, both external or one of each.

Note that the maximum total length of duct run where either one or two elbows are used is 3m

Kit 517FDK

Consists of:-

1 1.5m long duct.

1 1.5m long duct front cover

1 1.5m long duct backing plate

2 Duct support brackets with spacing washers

2 Woodscrews

2 Wall plugs

1 Joint cover

2 Spring cable clips

For use where a straight duct run up to 4.5m long is required.

No bends must be included in runs longer than 3m