SAFETY DATA SHEET



Leak Sealer 25 Ltrs

1. Identification of the preparation and of the company

	Product name	÷	Leak Sealer 25 Ltrs			
	Code	:	56748			
	Head Office	:	Cookson Electronics Forsyth Road Sheerwater Woking Surrey England GU21 5RZ Tel: +44(0)1483 758400 Fax: +44(0)1483 728837	Manufacturer	:	Cookson Electronics Forsyth Road Sheerwater Woking Surrey England GU21 5RZ Tel: +44(0)1483 758400 Fax: +44(0)1483 728837
	Contact person	:	shosken@cooksonelectronics.com			
	Material uses	:	Sealants			
)	Hazards	; [dentification			

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification

2

: Xn; R20

Effects and symptomsSkin contactSlightly hazardous by the following route of exposure: of skin contact (irritant).Eye contactSlightly hazardous by the following route of exposure: of eye contact (irritant).Toxicity dataNot available.See section 11 for more detailed information on health effects and symptoms.

3 Composition/information on ingredients

Ingredient name	CAS number	%	EC number	Classification
Europe				
Cellulose, carboxymethyl ether, sodium salt glycerol 1-stearate	9004-32-4 123-94-4	40 - 60 40 - 60	204-664-4	Xn; R20 Not classified.
See section 16 for the full text of the R-phrases declared above				

Occupational exposure limits, if available, are listed in section 8.

The classifications listed, indecate the potential hazards of the ingredients

4. First-aid measures

First-aid measures	
Inhalation	: Get medical attention if symptoms occur. If unconscious, place in recovery position and get medical attention immediately.
Ingestion	: Wash out mouth with water. Keep person warm and at rest. If unconscious, place in recovery position and get medical attention immediately.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.

: 23/09/2010.



Leak Sealer 25 Ltrs

4. First-aid measures				
Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.			
Protection of first-aiders	 No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. 			
Notes to physician	 No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. 			

See section 11 for more detailed information on health effects and symptoms.

5. Fire-fighting measures

Extinguishing media	
Suitable	: Use an extinguishing agent suitable for the surrounding fire.
Not suitable	: None known.
Special exposure hazards	: In a fire or if heated, a pressure increase will occur and the container may burst.
	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Hazardous combustion products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
Special protective equipment for fire-fighters	 Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

Personal precautions	: Use suitable protective equipment (section 8).
Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Large spill	: Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Note: see section 1 for emergency contact information and section 13 for waste disposal.
Small spill	: Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

7. Handling and storage

Handling	: Put on appropriate personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing.
Storage	 Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.
Packaging materials Recommended	: Use original container.



Exposure controls/personal protection 8.

Exposure limit values

Ingredient name

Europe glycerol 1-stearate

Sweden glycerol 1-stearate

Denmark

No exposure limit value known.

Norway silica, amorphous, fumed

France No exposure limit value known.

Netherlands No exposure limit value known.

Germany silica, amorphous, fumed

Finland silica, amorphous, fumed

United Kingdom (UK) silica, amorphous, fumed

Austria silica, amorphous, fumed

Switzerland silica, amorphous, fumed

Belgium glycerol 1-stearate

Spain glycerol 1-stearate

Turkey silica, amorphous, fumed

Czech Republic silica, amorphous, fumed

Ireland glycerol 1-stearate

Date of issue

Occupational exposure limits

ACGIH TLV (United States, 1/2008). TWA: 10 mg/m³ 8 hour(s). Form: Total particulate mass

AFS 2005:17 (Sweden, 6/2007). TWA: 5 mg/m³ 8 hour(s). Form: total dust

Arbeidstilsynet (Norway, 10/2003). TWA: 1.5 mg/m³ 8 hour(s). Form: respirable dust

MAK-Werte Liste (Germany, 7/2006). TWA: 0.3 mg/m³ 8 hour(s). Form: measured as the respirable fraction of the aerosol TRGS900 AGW (Germany, 1/2006). TWA: 4 mg/m³ 8 hour(s). Form: Inhalable fraction

Työterveyslaitos, Sosiaali- ja terveysministeriö (Finland, 4/2005). TWA: 5 mg/m³ 8 hour(s).

EH40-WEL (United Kingdom (UK), 9/2006). WEL 8 hrs limit: 6 mg/m³ 8 hour(s). Form: inhalable dust WEL 8 hrs limit: 2.4 mg/m³ 8 hour(s). Form: respirable dust

GKV_MAK (Austria, 6/2006). TWA: 0.3 mg/m³ 8 hour(s). Form: respirable fraction

SUVA (Switzerland, 2/2005). Notes: not temporary TWA: 4 mg/m³ 8 hour(s). Form: inhalable dust

Lijst Grenswaarden / Valeurs Limites (Belgium, 6/2007). TWA: 10 mg/m³ 8 hour(s).

INSHT (Spain, 1/2008). TWA: 10 mg/m³ 8 hour(s).

NIOSH REL (United States, 6/2001). TWA: 6 mg/m³ 10 hour(s). Form: All forms

178/2001 (Czech Republic, 6/2004). TWA: 0.1 mg/m³ 8 hour(s). Form: Respirable dust TWA: 4 mg/m³ 8 hour(s). Form: Total dust

NAOSH (Ireland, 8/2007). OELV-8hr: 10 mg/m³ 8 hour(s).

: 23/09/2010.



Leak Sealer 25 Ltrs	
8. Exposure con	trols/personal protection
Italy	
glycerol 1-stearate	ACGIH TLV (United States, 1/2008). TWA: 10 mg/m ³ 8 hour(s). Form: Total particulate mass
Estonia	Sataiaalministar (Estania, 0/2004)
silica, amorphous, fumed	Sotsiaalminister (Estonia, 9/2001). TWA: 2 MG/M3 8 hour(s). Form: inhalable dust
Lithuania	
glycerol 1-stearate	Del Lietuvos Higienos Normos (Lithuania, 10/2007). TWA: 5 mg/m³ 8 hour(s).
Slovakia	
silica, amorphous, fumed	Nariadenie Vlády Slovenskej republiky (Slovakia, 5/2006). TWA: 2 mg/m ³ 8 hour(s). Form: respirable compact aerosols TWA: 10 mg/m ³ 8 hour(s). Form: total compact aerosols
Hungary	
No exposure limit value known	
Poland	
No exposure limit value known	
Slovenia	
silica, amorphous, fumed	Uradni list Republike Slovenije (Slovenia, 4/2005). TWA: 4 MG/M3 8 hour(s). Form: Inhalable fraction
Latvia	
No exposure limit value known	
Greece	
No exposure limit value known	
Portugal	
glycerol 1-stearate	Instituto Português da Qualidade (Portugal, 3/2007). TWA: 10 mg/m³ 8 hour(s).
Recommended monitoring procedures	: Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances.
<u>Exposure controls</u>	
Occupational exposure controls	: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Respiratory protection	: Recommended: None assigned.
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. <1 hours (breakthrough time): disposable vinyl
Eye protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists o dusts. Recommended: safety glasses with side-shields EN 166 1F
Skin protection	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: overall
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipmen will be necessary to reduce emissions to acceptable levels.

Powered by

9. Physical and chemical properties

General information

Appearance

- to b o di di lo o	
Physical state	: Liquid.
Colour	: White.
Odour	: Characteristic.
VOC content	: 0 % (w/w) [ISO % 11890-2]

10. Stability and reactivity

_	
Stability	: The product is stable.
Conditions to avoid	: No specific data.
Materials to avoid	: No specific data.
Hazardous decomposition products	 Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. Toxicological information

Potential acute health effect		
Inhalation	Harmful by inhalation.	
Ingestion	Acute oral toxicity (LD50) Rat >2000 mg/Kg No known significant effects or o hazards.	critical
Skin contact	No known significant effects or critical hazards.	
Eye contact	No known significant effects or critical hazards.	
Acute toxicity		

Over-exposure signs/symptoms

12. Ecological information

Ac	ua	tic	ec	oto	xio	<u>ity</u> :
						_

Product/ingredient name Cellulose, carboxymethyl ether, sodium salt	Test -	Result Acute EC50 87.26 to 165.37 mg/L Fresh water	Species Daphnia - Water flea - Ceriodaphnia dubia - Neonate - <24 hours	Exposure 48 hours
	-	Acute LC50 >20000000 ug/L Fresh water	Fish - Rainbow trout,donaldson trout - Oncorhynchus mykiss - 25 to 50 g	96 hours
	-	Acute LC50 1000000 to 3300000 ug/L Marine water	Crustaceans - Common shrimp, sand shrimp - Crangon crangon - Adult	48 hours

Biodegradability Other adverse effects

: No known significant effects or critical hazards.

: 23/09/2010.



13. Disposal considerations

Methods of disposal	:	The generation of waste should be avoided or minimised wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.
European waste catalogue (EWC)	:	16 03 06 organic wastes other than those mentioned in 16 03 05
Hazardous waste	:	Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 91/689/EEC.

14. Transport information

International	transport	regulations
mennational	tranoport	rogalationo

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
ADR/RID Class	Not regulated.	-	-	-		-
IMDG Class	Not regulated.	-	-	-		-
IATA Class	Not regulated.	-	-	-		-

PG* : Packing group

15. Regulatory information

EU regulations

Classification and labeling have been determined according to EU Directives 67/548/EEC and 1999/45/EC (including amendments) and take into account the intended product use.

Hazard symbol or symbols



2

		namnu
Risk phrases	1	R20- Harmful by inhalation.
Safety phrases	:	S2- Keep out of the reach of children. S46- If swallowed, seek medical advice immediately and show this container or label.
Contains	:	Cellulose, carboxymethyl ether, sodium salt
Product use	:	Consumer applications, Industrial applications.
Other EU regulations		
Tactile warning of danger	:	Yes, applicable.
<u>Germany</u>		
Hazard class for water	:	2 Appendix No. 4
<u>ltaly</u>		
Emission control directive	:	Not classified.



Leak Sealer 25 Ltrs

16. Other information

Full text of R-phrases referred to in sections 2 and 3 - Europe	: R20- Harmful by inhalation.
Full text of classifications referred to in sections 2 and 3 - Europe	: Xn - Harmful
<u>History</u>	
Date of printing	: 20/07/2011.
Date of issue	: 23/09/2010.
Date of previous issue	: 29/07/2010.
Version	: 6
Prepared by	: Simon Hosken Environmental, Health and Safety Manager

✓ Indicates information that has changed from previously issued version.

<u>References</u>

The Health and Safety At Work Act 1974, section 6. Control of Substances Hazardous to Health (CoSHH) Regulations 2002 and its amendments.

Preparation contains soley TSCA and REACh 1907/2006 listed substances.

This safety data sheet has been prepared in accordance with the requirements of the Chemicals (Hazard Information and Packaging for Supply) Regulations 2002 which implement EC Directives 1999/45/EC and 2001/58/EC and their amendments.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

