





## DRT1 & DRT2

## **Digital Room Thermostats**

Battery powered

Replaces existing thermostat with no additional wiring Energy saving

### ROOM THERMOSTAT - DRT 1

Ideal for combi boilers with built in time control

Upgrades to existing stats on a gravity system

Ideal temperature control for mutliple zone systems

#### **PROGRAMMABLE THERMOSTAT - DRT 2**

Ideal for combi boilers

Upgrades to existing stats on a fully pumped system

Horstmann. Together, we're in control.


## Horstmann. Together, we're in control.




# ROOM THERMOSTAT Model DRT 1

With an adjustable temperature range of between 5°C to 35°C, the Horstmann DRT1 is suitable for all central heating systems, its simple 2 wire connections and battery powered operation allows the DRT1 to be used on mains or low voltage switching.

Dimensions Shown in mm





#### **SPECIFICATION**

### ROOM THERMOSTAT

TYPE DRT 1

OPERATING VOLTAGE

230V 50/60Hz

SWITCH CURRENT AT 250V AC
5 (3) Amps Maximum

CONTACT CONFIGURATION

SPDT

TEMPERATURE RANGE
+5°C to +35°C

SWITCHING DIFFERENTIAL

Approx. 1°C
BATTERY LIFE
In excess of 2 years
IP 30

## ROOM THERMOSTAT TYPE DRT 2

PROGRAMMES

4 Weekday

2 Saturday2 Sunday

OPERATING VOLTAGE

230V 50/60Hz

SWITCH CURRENT AT 250V AC

5 (3) Amps Maximum

CONTACT CONFIGURATION

SPDT

TEMPERATURE RANGE

+5°C to +35°C

SWITCHING DIFFERENTIAL

Approx. 1°C

**BATTERY LIFE** 

In excess of 2 years

IP 30





# PROGRAMMABLE THERMOSTAT Model DRT 2

The Horstmann DRT2 programmable room thermostat has all the features of the DRT1, whilst offering flexible programming. This allows the user to set different temperature levels at different times of the day to suit the daily routine of the household.

(4 time and temperature programmes Monday to Friday, 2 time and temperature programmes for each of the weekend days.)

Dimensions Shown in mm





Both the Horstmann DRT1 and DRT2 thermostats are fully compatible with Horstmann Valves and Programmers.

