


## Wheelhandle Angle Towel Rail valve for copper



### GENERAL INFORMATION

| Size       | Pattern No.               | Box Qty | Code   | Barcode       | Price (£) ex VAT |
|------------|---------------------------|---------|--------|---------------|------------------|
| 15mm x 1/2 | WH Angle Towel Rail valve | 1       | 632201 | 5013866073748 | £14.70           |
| 10mmx1/2   | WH Angle Towel Rail valve | 1       | 632202 | 5013866073762 | £14.70           |

### DIMENSIONS (mm)

| Code   | Description                                | A  | C       | D  |
|--------|--|----|---------|----|
| 632201 | 15mmx1/2 WH Terrier Angle Towel Rail Valve | 30 | 54 open | 62 |
| 632202 | 10mmx1/2 WH Terrier Angle Towel Rail Valve | 29 | 54 open | 62 |

### PRESSURE & TEMPERATURE

| Wheelhead Angle Pattern                           | Minimum Operating Pressure (bar) | Maximum Cold Working Pressure (bar)  | Maximum Hot Working Pressure (bar)            |
|---|----------------------------------|--------------------------------------|---|
| TERRIER 1/2X15MM ALL CP WH ANGLE TOWEL RAIL VALVE | No Minimum Operating Pressure    | 10.0 bar at temperatures up to 120°C | Not Suitable for Maximum Hot Working Pressure |

### CARE & MAINTENANCE

#### Care

To maintain the surface finish, simply wipe occasionally with a mild detergent on a soft damp cloth. Dry using a soft cloth. Never use abrasive cleaners or chemical household cleaners and avoid contact with concentrated bleach.

#### Maintenance

No maintenance is required for this product.

For any further help please contact the Service Support Team on: 0800 1560050.

### REGULATIONS

#### Regulations

Terrier thermostatic radiator valves are approved to EN 215. For valves with compression connections, the connections are approved to BS EN1254-2; threaded connections comply with BS 21 or BS 2779.

They are designed for use only in an indirect open-vented or sealed water-filled central heating and/or indirect hot water system and for no other purpose.

They must be used within the pressure and temperature limits stated in the technical information table below.

| Operating Conditions               | Maximum |
|------------------------------------|---------|
| System Water Temperature (at 5bar) | 120 °C  |
| Operating pressure (at 65°C)       | 10 bar  |

Under no circumstances must they be used in systems containing liquids or solutions other than water. The only exception is the addition of a proprietary central heating corrosion inhibitor, cleaner or anti-freeze to the system water in accordance with the manufacturer's instructions.

Terrier heating controls are manufactured to a strict quality assurance system in accordance with ISO 9000: 2001.

### GUARANTEE

#### Thermostatic and Manual Radiator Valves

#### Pegler Yorkshire Customcare 5 Year Guarantee - Terms & Conditions

Products are subject to a 5 year guarantee that is between Pegler Yorkshire and the final purchaser of the product.

The guarantee is subject to proof of purchase being supplied.

This guarantee does not affect any statutory rights the consumer may have in law.

The guarantee covers manufacturing or material defects and is not applicable where the product is fitted contrary to conditions of use in our literature.

The guarantee is subject to the following limitations:

1. The valves are designed for use only in an indirect open-vented or sealed water-filled central heating and/or indirect hot water system and for no other purpose.
2. They must be used within the pressure and temperature limits stated in the technical information table below.

Operating Conditions (Maximum)  
System Water Temperature (at 5bar) : 120 °C

Operating pressure (at 65 oC) :10 bar

3. Under no circumstances must they be used to in systems containing liquids or solutions other than water. The only exception is the addition of a proprietary central heating corrosion inhibitor, cleaner or anti-freeze to the system water in accordance with the manufacturer's instructions.

4. Damage caused by abusive behaviour and accidental damage to the product are not covered by this guarantee

The extent of Pegler Yorkshire liability is limited to the cost of the replacement of the defective item and not to fitting or consequential damages.