Bostik

SAFETY DATA SHEET RAPID REPAIR MORTAR

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME	RAPID REPAIR MORTAR
PRODUCT NO.	540033, 540040
SUPPLIER	BOSTIK LIMITED COMMON ROAD STAFFORD STAFFORDSHIRE ST16 3EH +44 1785 255141 +44 1785 272650 (24Hour Emergency) sds.uk@bostik.com

2 HAZARDS IDENTIFICATION

Irritating to skin. Risk of serious damage to eyes. May cause sensitisation by skin contact.

CLASSIFICATION

Xi;R38, R41. R43.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
CALCIUM HYDROXIDE		1305-62-0	5-10%	Xi;R38,R41.
PORTLAND CEMENT	266-043-4	65997-15-1	30-60%	Xi;R38,R41.

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

INHALATION

Remove victim immediately from source of exposure. Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

INGESTION

DO NOT induce vomiting. Get medical attention immediately.

SKIN CONTACT

Promptly flush contaminated skin with water. Promptly remove clothing if soaked through and flush the skin with water. If possible use warm water. Get medical attention promptly if symptoms occur after washing.

EYE CONTACT

Rinse the eye with water immediately. Continue to rinse for at least 15 minutes and get medical attention.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Use fire-extinguishing media appropriate for surrounding materials.

SPECIFIC HAZARDS

Fire creates: Toxic gases/vapours/fumes of Carbon monoxide (CO). Carbon dioxide (CO2).

6 ACCIDENTAL RELEASE MEASURES

RAPID REPAIR MORTAR

PERSONAL PRECAUTIONS

Avoid skin and eye contact. Wear personal protective equipment. Ensure adequate ventilation. Avoid breathing vapour

ENVIRONMENTAL PRECAUTIONS

Prevent entry into drains and water courses.

SPILL CLEAN UP METHODS

Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS Avoid spilling, skin and eye contact. Avoid breathing dust

USAGE DESCRIPTION *IMPORTANT* Use within time period as indicated on packaging.

STORAGE PRECAUTIONS

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

STORAGE CLASS

Chemical storage.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

PROTECTIVE EQUIPMENT



ENGINEERING MEASURES

Well-ventilated area.

RESPIRATORY EQUIPMENT

Wear mask supplied with: Dust filter P3 (for especially fine dust/powder).

HAND PROTECTION

Protective gloves must be used if there is a risk of direct contact or splash. Use protective gloves made of: Nitrile.

EYE PROTECTION

Wear dust resistant safety goggles where there is danger of eye contact.

OTHER PROTECTION

Provide eyewash station. Wear appropriate clothing to prevent repeated or prolonged skin contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap & water if skin becomes contaminated. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES			
APPEARANCE	Powder, dust		
COLOUR	Grey		
BULK DENSITY	1200-1600 kg/m3	pH-VALUE, DILUTED SOLUTION	12-14 when wet

10 STABILITY AND REACTIVITY

RAPID REPAIR MORTAR

STABILITY

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid contact with strong oxidisers.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

11 TOXICOLOGICAL INFORMATION

INHALATION

Irritating to respiratory system.

INGESTION

May cause discomfort if swallowed. May cause stomach pain or vomiting.

SKIN CONTACT

May cause serious chemical burns of the skin. May cause an allergic reaction.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Not regarded as dangerous for the environment. However, contamination of the aquatic or terrestrial environments should be avoided

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION		
GENERAL	The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).	
MARINE POLLUTANT	No transport warning sign required. No.	

15 REGULATORY INFORMATION

LABELLING

×
Irritant

RISK	PHRASES	

RISK PHRASES		
	R38	Irritating to skin.
	R41	Risk of serious damage to eyes.
	R43	May cause sensitisation by skin contact.
SAFETY PHRASES		
	S2	Keep out of the reach of children
	S24/25	Avoid contact with skin and eyes.
	S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
	S46	If swallowed, seek medical advice immediately and show this container or label.
	S56	Dispose of this material and its container to hazardous or special waste collection point.

RAPID REPAIR MORTAR

S64	If swallowed, rinse mouth with water (only if the person is conscious).
S36/37/39	Wear suitable protective clothing, gloves and eye/face protection.
S22	Do not breathe dust.

STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations. Control of Substances Hazardous to Health.

APPROVED CODE OF PRACTICE

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

GUIDANCE NOTES

CHIP for everyone HSG(108). Workplace Exposure Limits EH40.

16 OTHER INFORMATION

GENERAL INFORMATION

This product should be used as directed by Bostik Ltd. For further information consult the product data sheet or contact Technical Services.

INFORMATION SOURCES

This safety data sheet was compiled using current safety information supplied by distributor of raw materials.

REVISION COMMENTS

This safety data sheet supersedes all previous issues and users are cautioned to ensure that it is current. Destroy all previous data sheets and if in doubt contact Bostik Limited.

ISSUED BY

Approved EC

REVISION DATE July 07

REV. NO./REPL. SDS GENERATED 1

DATE

RISK PHRASES IN FULL

R38	Irritating to skin.
R41	Risk of serious damage to eyes.

July 07